

FIG. 1A




FIG. 1B




FIG. 1C




FIG. 10

Universal Frequency
Translation (UFT)
module 202

Port 2

204

204

206

FIG. 2A




Fig. 2B






FIG. 3

=1G. 4

Universal Frequency
Up-conversion
(UKFU) Module 590)




FIG. 3


FIG BH

FILTERED OUTPUT SIGNAL

HARMONICS OF SIGNALSSAIO AND 1/2 (SHOWN SIMULTANFOUSLY BUT NOT SUMMED)

FIG 6 Cont

W



FI6.7





FIG. 8



FI6.9




FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 14





FIG. 15A





W




FIG. 1SF




FIG. 16




FIG. 17

Time	(rising edge		t-1 (rising edge of ∳₂)		t (rising edge of ϕ_1)		t (rising edge of ∳₂)		t+1 (rising edge of φ₁)	
Node 1902	VI _{t-1}	Ψ ₁ / 1804	VI _{t-1}	1608	VI _t	<u>1816</u>	VI _t	<u>1826</u>	VI _{t+1}	<u>1838</u>
1904			VI _{t-1}	<u>1810</u>	VI _{t-1}	<u> 1818</u>	V۱ _t	<u>1828</u>	VI _t	<u>1840</u>
1966	VO _{t-1}	1806	VO _{t-1}	<u>1812</u>	VO _t	<u>1820</u>	. VO _t	<u>1830</u>	VO ₁₊₁	184z
1908	1_		·VO _{t-1}	· <u>1814</u>	VO _{t-1}	<u>1822</u>	VO _t	<u>1832</u>	VO,	<u>1844</u>
1910	_	1807	_		VO _{t-1}	<u>1824</u>	VO _{t-1}	<u>1834</u>	VO,	<u>1846</u>
1912	-		_	<u>1815</u>	_		VO _{t-1}	<u>1836</u>	VO _{t-1}	1848
1918	-		_		_				VI _t - <u>1850</u> 0.1 * VO _t - 0.8 * VO _{t-1}	

FIG. 18

FIG. 19.

F19. 20A




FIG. 20A-1





FIG. 20B

FIG. 20C

FIG. 200

FIG. 20E

FIG. 20F



42-389 - AM SPECIALE WHITE S SOUNCE 42-382 - TOD RECYCLED WHITE S SOUNCE 43-480 - TOD RECYCLED WHITE S SOUNCE 44-480 - TOD RECYCLED WHITE S SOUNCE

W

A STE TO RECYCLED WHITE & SOULKE ASSUME ASSUME BOUNES


Ŋ


W


43.552 IORECYCLED WHITE S SOUNCE 42.550 200 RECYCLED WHITE S SOUNCE WHITE S SOUNCE WHITE S SOUNCE WAS A STATE OF THE STATE

\$\tau_{1} \text{first } \text{II} \text{ \text{first } \text{ \text{first } \text{ \text{first } \text{ \text{first } \text{ \text{ \text{first } \text{ \ \text{ \text{ \text{ \text{ \text{ \text{ \text{ \text{ \text{ \

W








FE6.24K

: *_{2,}{-



. . . .

2500

Fz6,25B

haseband signal 2526




FIG. 25C




FIG. 250





FIG. 258



F16.251

FIG 256




FIG 25 H




FIG. 25I




FIG. 25J






FIG. ZGA


THE SOURCE STATE OF SECTION OF STATE OF


The control of the co





FIG



























FIG. 28]

13-7182 500 SHEETS, HILLY S.J.
42-381 50 SHEETS, SHEET

Brance Religion of Brance

FZG. 29








FIG. 3/18






3430







Netlonel *









Aperture = 500psFundamental Clock = 200Mhz (5th Subharmonic)

Square Wave Frequency = 200Mhz








FIG.3SJ





FIE. 36B





3753

FIG. 42A





FIG. 42B






FIG 43B: Mobile IS-55 Requirements






FIG. 44 : Convertional Transmitter

National Brand 2-20 May Physics C HLLI 2-20 May Physic

.

National **





FIG. 454 ; CDMA Transmitte



42.381 42.382 42.389 42.399 42.399








	Fre. 450

National Brand 42

A2-391 SSEREIS FYE-LASSE S STANKE A2-382 TOS SEREIS FYE-LASSE S SCHAME A2-382 TOS SEREIS FYE-LASSE S SCHAME A2-382 TOS SEREIS FYE-LASSE SCHAME A2-382 TOS SECUCIED WHITE S CALAME MESHAD 20.





Fis. 45E





FIG: 45F CDMA Transmitter



FIG 463 COMA CMOS CHIP








Base Station


48027 RHO 0.9970 **EVM** 5.51% FIG. 48 PHASE ERROR 1.80° MAGNITUDE 4.53% **ERROR CARRIER** -37.91 dB **INSERTION** PA POWER OUT 28.06 dBm

	LOW	MIDDLE	HIGH	r
RHO	0.9892	0.9969	0.9892	
EVM	10.39%	5.54%	10.39%	
PHASE ERROR	4.47°	2.24°	4.08°	
MAGNITUDE ERROR	6.84%	4.21%	8.27%	
CARRIER INSERTION	-40.15 dB	-44.58 dB	-35.27 dB	
PA POWER OUT	27.36 dBm	28.11 dBm	27.55 dBm	


FIG. 49




Base Station Constellation for Pilot Channel Test




Base Station Sampled Constellation



Mobile Station Constellation for Access Channel Test




Mobile Station Sampled Constellation



Base Station Constellation using only H/P Test Equipment

ា បរាំព្រះមាននំ។



Mobile Constellation using only H/P Test Equipment





FIG. 56

73. E



Base Station Spectral Response with Mask

PIG. 57




FIG. 58





Figure 3.2-2 Mobile Station Spectral Response with Mask




CDMA Crosstalk


FIG 60A

Sequence for IQ Input Level Variance












FIG. GOD






FIG. 60F


The train and then the first of


C





Sequence for LO Variance


























FIG. 60M














Sequence for IQ Input Level Variance














Sequence for LO Variance

F-1

TG 60U








Figure 3.6-6


FIG. GOV












Quantity	Description	Voltage	Total Current	Power
2	D2D Cores	3.3	4mA	13.2mW
2	Baseband Interface Circuits with/BW Limit	3.3	бтА	21.8mW
1	Clock Circuit	3.3	5mA	20.0mW
	·		Sub Total	54.0mW

FIG. 602





·..;

Hall Bar H. Who gain from the H. Gran dead repeat space three states of the H.












PIE. 63A








TC 630

Cumbines 6310

__



Frequency

n/Ts

3/75


2/12


1/Ts






A H. J. H. H. Harre Harry M. H. Harry Harr










FIG. 70





FIG. 7/A



FI6.71B







FIG. 72A










A rising edge pulse generator

FIG. 73D



B. falling-edge pulse generator








FIG. 744



FI6.74B










FIG. 78A







FIG. 78B





8102 - Switch module
8104 9108
FIG. 81A



5




FIG. 81C





FIG. 81D

A. rising edge pulse generator






B. falling-edge pulse generator

FIG. 82B

Input Signal

Twenter 8238

FIC 83C








Fig 84 - Impedance Matched Aliasing Module

· [7]


FIG. 85.A

-





F16. 88A



State Machine Flowchart

F19.88B

F1G.88C


THE THE THE THE REAL PROPERTY.


ĻĦ


. 3

= -


...








F19.94




F.9,95


.....




H 10	* C:\MSim (8\) (A) patl.d (A) patl.d (B)	8\Gribjedjedkiwirauzsk\baztzski	dat	F19,963 \\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\				200ns 250ns 300ns 350ns 400ns
------	--	---------------------------------	-----	--	--	--	--	-------------------------------



ک








single-series-switch-915M-5M-hieff.sch


FIG. 10

--




CKT@915MHz/101.1MHzCLK (-63db p-p available power) .02ns step

single-series-switch-smaperture915M-5M-hieff.sch



single-series-switch-bypass-915M-5M-hieff.sch

single-series-switch-wobypass-915M-5M-hieff.sch






FIG. 107.A

$$q = C \cdot V$$

EQ. 10

$$V = A \cdot \sin(t)$$

EQ. 11

$$q(t)=C\cdot A\cdot \sin(t)$$

EQ . 12

$$\Delta q(t) = C \cdot A \cdot \sin(t) - C \cdot A \cdot \sin(t - T)$$

EQ.13

$$\Delta q(t) = C \cdot A \cdot (\sin(t) - \sin(t - T))$$

EQ. 14

$$\sin(\alpha) - \sin(\beta) = 2 \cdot \sin\left(\frac{\alpha - \beta}{2}\right) \cdot \cos\left(\frac{\alpha + \beta}{2}\right)$$

$$\Delta q(t) = 2 \cdot C \cdot A \cdot \sin \left[\frac{t - (t - T)}{2} \right] \cdot \cos \left[\frac{t + (t - T)}{2} \right]$$

EQ.16

$$\Delta q(t) = 2 \cdot C \cdot A \cdot \sin\left(\frac{1}{2} \cdot T\right) \cdot \cos\left(t - \frac{1}{2} \cdot T\right)$$


$$= \mathbb{Q} \cdot 17$$

$$q(t) = \int_{-\infty}^{\infty} C \cdot A \cdot (\sin(t) - \sin(t - T)) dt \qquad \text{Eq. 18}$$

$$q(t) = -\cos(t) \cdot C \cdot A + \cos(t - T) \cdot C \cdot A$$
 EQ. 19


$$q(t)=C\cdot A\cdot (\cos(t-T)-\cos(t))$$

EQ. 20



-IG. 101C

For Graph 2: C=1, A=.5, $T=\pi/10$:



Graph 2

FIG. 100, D

Power-Charge Relationship

$$P = \frac{q^2}{C \cdot S}$$

FIG. 107, E

Week that all enter than each offer that out it was one out it.

Insertion Loss

Insertion loss in dB is expressed by:

or

ILdB=10·log
$$\frac{\left|\frac{\operatorname{Vin}^{2}}{\operatorname{Rin}}\right|}{\left|\frac{\operatorname{Vout}^{2}}{\operatorname{Rout}}\right|}$$